



**The Clear Choice**  
Water Filtration Systems

# FCCBL-S-TW

**2,5" Speciality in-line TWIST TYPE  
Filter Cartridge with bituminous  
and coconut shell activated carbons**

## General Description:

**AQUAFILTER FCCBL-S-TW (SILVER)** series are state-of-the-art carbon blocks. They were designed to fit white 2.5" in-line **TWIST TYPE** housing. Cartridges are made of a mixture of high quality bituminous and coconut shell activated carbons, which comply to the strict **FDA standards**.

Moreover a special heavy metal removal media was utilized.

It effectively removes lead, copper, mercury, strontium, etc.

**FCCBL-S-TW** series carbon blocks effectively removes free chlorine and its derivatives and many organic substances improving taste and odor of water. Small micron rating makes them effective sediment cartridge, which removes sand, silt, rust and suspended solids from filtered water.


**FCCBL-S-TW** effectively protects drinking water supplying systems. Cartridges are dedicated for cold potable water filtration.

**FCCBL-S-TW** features easy twist-off filter four stage 1/4 turn encapsulated cartridge, all designed to make installation and replacement quick, easy and sanitary.

Each cartridge is pressure tested.

## Features:

- High quality
- Competitive Pricing
- Made of safe, food grade materials
- Cartridges are removed with a simple 1/4-turn
- Contains a mixture of bituminous and coconut shell carbons
- Removes free chlorine and its derivatives
- Removes organic contamination (benzene, toluene)
- Removes heavy metals (Pb, Cu, Hg, Sr, Cs)
- Removes chlorine, its derivatives and organic substances
- Softens water (improving scale reduction)
- Improves taste and odor of water
- Excellent filtration at small pressure drops
- Small orders accepted
- Made in EU with High Quality materials
- Component NSF Certified and FDA CFR Title 21 Compliant
- Cartridges are attractively labeled
- Easy Cartridge Replacements!



### NOTE

- Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.
- We strongly recommend regularly scheduled maintenance and replacement of the filter cartridge in order for the product to perform properly.
- Replace the filter cartridge at least every 3 or 6 months (depending on water quality).
- Water filtration systems can help reduce the presence of microorganisms or other contaminants with potential health effects.

**LIMITED WARRANTY:** AQUAFILTER warrants that this product is free from defects in materials and workmanship. This limited warranty does not apply to failures that result from abuse, misuse, alteration or failure to properly comply with installation or cartridge change instructions and water quality.



\* Cartridges Available for Sale with Cap

CAT #	Size	Max. Flow		Filter life* months
		lpm	gpm	
FCCBL-S-TW	12" x 2.5" (313 mm x 67 mm)	2.8	0.75	3 - 6
FCCBL-S-TW-CP	12" x 2.5" (325 mm x 82 mm x 14 mm)	2.8	0.75	3 - 6
FCCBL-S-TW-CP2	12" x 2.5" (338 mm x 82 mm x 14 mm)	2.8	0.75	3 - 6

\* filter cartridge lifetime based on contamination level of potable water.



Made in EU

All Aquafilter images, trademarks, logos, and other intellectual property are the sole and exclusive property of Aquafilter, Inc. and may not be used without our express written permission.

**Aquafilter  
Manufacturing  
Facility**



**Aquafilter Inc.**  
Hunt Valley 21030, USA

us@aquafilter.com



**Aquafilter Germany**  
15234 Frankfurt, Germany

de@aquafilter.com



**Aquafilter Europe**  
91-222 Lodz, Poland

pl@aquafilter.com

