



The Clear Choice
Water Filtration Systems

www.aquafilter.com



FCCBL-S

Mixed Activated Carbon and softening cartridge


Aquafilter offers **FCCBL-S** cartridges (**FCCBL5-S, FCCBL-S, FCCBL10BB-S, FCCBL-L-S** and **FCCBL20BB-S**) suitable for POU (Point of Use) and POE (Points of Entry) installations. Through its accurate combination of mixed granular activated carbon (GAC) media, FCCBL-S series improves the bad taste and odor of your drinking water by reducing the concentration of chlorine and organic compounds (VOC's). Additionally, the cation exchange-based resin water softening process is performed by the decrease of calcium and magnesium content, enhancing the obtaining of fresh and clean drinking water.

SYSTEM CONTENT & SPECIFICATIONS

- Cartridge Media: Mixed Bituminous and Coconut shell GAC and cation exchange-based resin
- Cartridge operating pressure: 6 bar (90 psi)
- Water system temperature range: 2 – 23 °C (35 – 73.4 °F)
- Cartridge material: Polypropylene (end caps), silicone (gasket), LDPE (body)



CAT#	DIMENSIONS inches (mm)
FCCBL5-S	4 7/8 x 2 1/2 (124 x 69)
FCCBL-S	9 7/8 x 2 1/2 (250 x 69)
FCCBL-L-S	20 x 2 1/2 (508 x 69)
FCCBL10BB-S	9 7/8 x 4 1/2 (250 x 105)
FCCBL20BB-S	20 x 4 1/2 (508 x 105)



IMPORTANT NOTICE: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection. Release air and flush the filter before use by running cold water through any faucet for 2-5 minutes - new cartridges may release a very fine powder after installation. Proper installation into the housing is necessary for filtration to occur and an arrow on the cartridge indicates the required flow direction. For the product to perform properly we recommend regularly scheduled maintenance and replacement of the filter cartridge. Filters may need to be replaced more frequently than specified based on water consumption and contaminants in your water supply. A decrease in water pressure may indicate that a filter may have become clogged. It is recommended that you keep a "Filter Replacement Log" attached to your system to record the date of filter changes. Beware of purchasing low-cost products from unknown sources as they do not represent our high standards for design, materials or quality. If you choose to purchase and use a look-alike product with a price far below ours it is a clear indication you need to take care regarding safety. **LIMITED WARRANTY:** Aquafilter warrants that this product is free from defects in materials and workmanship. This warranty, together with any and all warranties implied by law, shall be limited to a period of time specified on each product warranty card. Improper installation and maintenance may result in property damage. This limited warranty does not apply to failures that result from abuse, misuse, alteration or failure to properly comply with installation or cartridge change instructions. We strongly recommend adding a Pressure Limiting Valve to guard against extreme water pressure at point of use and point of entry to avoid surges and water hammering due to an increase in water pressure. Any damages claimed from failing to install a Pressure Limiting Valve will be denied. All Aquafilter images, trademarks, logos, and other intellectual property are the sole and exclusive property of Aquafilter and may not be used without our express written permission.



Aquafilter Europe
ul. Sw Teresy 101
91-222 Lodz, Poland
sales@aquafilter.com



Made in EU